


## Bead Chain/Cord Tension Lock Installation Instructions

**Always keep the bead chain and cord loops secure and out of reach of children and pets.**


### Step 1 Attach the Bracket to Cord Tension Lock

#### Outside Mount



Insert the nub of the Bracket into the Cord Tension Lock and secure with small screw provided


#### Inside Mount



Insert the nub of the Bracket into the Cord Tension Lock and secure with small screw provided


### Step 2 Mark Mounting Position

#### Step 1




With the Shade securely installed pull the chain taut in the window opening with the bracket against the mounting surface

#### Step 2



Make sure the bracket's screw hole is aligned with the horizontal mark on the Tension Lock

#### Step 3



While holding the lock firmly in place, check if the loop can move freely through it and then mark holes


If the Tension Lock locks onto the loop, it is too loose and the bracket and lock should be moved down

If the loop does not run freely through the lock, it is too tight and the bracket and lock should be moved up

### Step 3 Attach the Bracket to Mounting Surface


Attach to mounting surface using the two longer screws provided

#### Outside Mount



The Bracket will need to be removed from the Tension Lock to install

#### Inside Mount



Cord Tension Lock removed for clarity


Re-attach the Tension Lock to the Bracket and test the operation of the Tension Lock

Make sure the Cord Tension Lock is not placed in the path of the bottom rail or fabric

## P-Clip Safety Tensioner Installation Instructions

### Step 1 Install the Chain or Cord

#### Step 1




Squeeze the P clip together to close it

#### Step 2



Slide Chain or Cord into the P-Clip




#### Step 3



With the shade securely installed, pull the chain taut and mark the location on the mounting surface

### Step 2 Install the Tensioner

The P-Clip Safety Tensioner can be installed in a few different orientations. Choose one that best suits your needs and make sure that the cord or chain is taut and moves freely through the Tensioner



Then secure to the mounting surface using the screw provided

Make sure the P-Clip Safety Tensioner is not placed in the path of the bottom rail or fabric

It is imperative that the Tension Lock for bead chain or cord loops is properly secured to the wall or window frame to reduce a child's access to the chain or cord loops.

Young children and pets can wrap chains around their necks and strangle themselves.