

# Aerosmith Fastening Systems

## **VERSAPIN™** FASTENING SYSTEM

### ST4200

#### Features

- † Lightweight - only 4.8 lbs
- † Depth of Drive Adjustment
- † 360° adjustable exhaust deflector
- † Uses Aerosmith brand flat wire welded fasteners
- † Anti-Double fire mechanism
- † Trigger Lock to prevent accidental firing
- † Anti-Skid pad
- † Shock absorbing comfort rubber handle
- † Belt Clip
- † Comes with plastic carrying case



#### Applications

- † Plywood to Steel 14-18 ga (68-43 mil)
- † Exterior Gypsum to Steel 14-18 ga (68-43 mil)
- † Cement Fiber Board to Steel 14-18 ga (68-43 mil)
- † Steel to Steel 14-18 ga (68-43 mil)
- † Stucco Lath Applications 14-18 ga (68 - 43 mil)

#### Specifications

|                                |  |
|--------------------------------|--|
| Height                         | 11-1/4" (285 mm)   |
| Width                          | 4-2/5" (112.2 mm)  |
| Length                         | 9-1/2" (241.5 mm)  |
| Weight                         | 4.8 lbs (2.2 kgs)  |
| Recommended Operating Pressure | 70-120 psi (4.9-8.3 bar)                                   |
| Air Consumption                | 2.86 s.c.f.m. (60 cycles/minute)<br>1.35L/cycle at 100 psi |
| Loading Capacity               | Up to 200 fasteners  |

#### Fastener Specifications

|                            |                                  |
|----------------------------|----------------------------------|
| Wire Welded Coil Fasteners | 3/4" – 1-1/2" (19-38 mm)         |
| Shank Diameter             | .100" (2.54 mm)                  |
| Head Diameter              | .197" - .312" (5.0 – 6.4 mm)     |
| Recommended Fasteners      | Aerosmith Helical, Gripshank     |
| Accessories                | Magnetic washer adapter UNM4100A |