




Aerosmith High Pressure Flooring Pins



HN120

Fast. . Lightweight. . Powerful!

The Next Generation for Plywood Subfloor and Underlayment to Concrete



- † Powerful enough to drive .300" head pins into concrete, steel and even 6,000 PSI concrete
- † Easily fasten subfloor, underlayment and sleepers to concrete
- † 75 pin count coils for less reloading
- † Ultra Light weighing 6.4 lbs., Low Recoil
- † Free of Powder Load, No Licensing Required
- † Low Recoil
- † Adjustable magazine allows 1"-2-1/2" pin lengths
- † Run High Pressure and Conventional tools from one, lightweight compressor

The FASTEST way to penetrate concrete.



Aerosmith pins ensure consistent and durable fastening.



Power PIN[®]

Call 1-800-528-8183 or visit us online at www.AerosmithFastening.com.

An **aerosmith[®]** Product...

**Defining the Standard
for Steel & Concrete
Fastening**

Your Local Authorized Aerosmith Distributor

Aerosmith Fastening Systems
5621 Dividend Road, Indianapolis, IN 46241
Ph: 317.243.5959 Fax: 317.390.6980
Email: questions@AerosmithFastening.com
www.AerosmithFastening.com

Use Aerosmith Pins in Your High Pressure Tools

Aerosmith has pins for your High Pressure tools. Aerosmith .145HP pins are designed to attach Hardwood Floor underlayment faster and safer than traditional methods.

.145 Series, Knurled and Smooth Shank Plastic Sheet Coil Collated

Shank Diameter = .145" Head Diameter = .300" Knurled Shank - Zinc Galvanized G=PT2000 (2000 hour)



Reports and Approvals Available at www.Aerosmithfastening.com

PER Report 07021
ICC / ICBO ESR-3453



ITEM	LENGTH	KNURL	CARTON	APPLICATION
5323HP	1-1/4" (32mm)	Smooth	1.5 M	Plywood and Sport Track
5323HPG	1-1/4" (32mm)	Smooth PT2000	1.5 M	Pressure Treated Plywood and Sport Track
5323HPST	1-1/4" (32mm)	Smooth Step	1.5 M	Plywood and Sport Track
5383HP	1-1/2" (38mm)	Smooth	1.5 M	Plywood
5503HP	2" (50mm)	Smooth	1 M	Underlayment to Plywood Subfloor to Concrete
5573HP	2-1/4" (57mm)	Smooth	1 M	Sleeper and Dim. Lumber
5573HPG	2-1/4" (57mm)	Smooth PT2000	1 M	Sleeper and Dim. Lumber
5633HP	2-1/2" (63mm)	Smooth	1 M	2X4 to Concrete
5633HPG	2-1/2" (63mm)	Smooth PT2000	1 M	PT and Fire treated 2X4 to Concrete

Tool, Compressor and Accessories



500 PSI Compressor
High pressure compressor designed to operate High Pressure tools and regular pressure tools at the same time. **WEIGHS 51 LBS!** (AKHL1260EX)



Yellow Outlets Regular Pressure



Orange Outlets High Pressure



HN120 Swivel Hose Fitting



Wide range of fastener length with adjustable magazine plate. 1" to 2-1/2" pin accommodation



Air Hose and Fittings

High pressure hose and fittings are designed exclusively for High Pressure tools. 100 ft./30 mm (KHL100FT) and 50 ft./30mm (KHL50FT) High Pressure Hoses.

Aerosmith Fastening Systems
5621 Dividend Road, Indianapolis, IN 46241
Ph: 317.243.5959 Fax: 317.390.6980
Email: questions@AerosmithFastening.com
www.AerosmithFastening.com



Aerosmith Fastening Systems (Aerosmith) does not practice structural engineering, or architectural / building design, and is not responsible for the recommendation or use of its products in situations where a professional or certified opinion is required. It is the responsibility of the end user to comply with all local building codes, project design specifications, and good building practices. For the use of building professionals, Aerosmith does provide third party evaluation reports and engineered test data performed to recognized protocols.

Reorder Number: HP144HW-12-14