

Aerosmith PT2000 Fastener

The Best Just Got Better!

Testing shows the alloy plating technology of PT2000™ to have 3 to 10 times* the corrosion resistance conventionally achieved with electro or hot dip galvanizations. Aerosmith PT2000 Fasteners' distinctive finish offers optimum protection in applications demanding high corrosion resistance.

*comparative results based on averages from over 4 different plating types, in pressure treated wood, using protocol ASTM B117

Protocol	Aerosmith PT2000 Fastener	Name Brand Hot Dip Galvanized	Multi Electro Galvanized	Other Misc. Weather/Corrosion Resistant Coatings
ASTM B117	2000	642	376	458
ASTM B117 Modified (Fasteners Driven into pressure treated board)	1656	412	N/A	180
Fasteners Immersed directly into 6% ACQ Solution	125	43	48*	24



PT2000™ fastener after 1008 hours salt spray



Name Brand hot dip galvanized fastener after 1008 hours salt spray

Applications:

- † Pressure Treated Woods
- † CFB Siding
- † Furring
- † Composites
- † Coastal Applications
- † Metal to Concrete
- † Select Industrial Applications

Aerosmith PT2000™ Fastener Benefits:

- † Shortens job time and increases profits
- † Exceptional corrosion resistance retained after fasteners are driven
- † The speed, value, and variety of Aerosmith Fastening Systems (7 times faster than screws)
- † Fastener code approvals

Aerosmith Fastening Systems
5621 Dividend Road, Indianapolis, IN 46241
Ph: 317.243.5959 Fax: 317.390.6980
Email: info@AerosmithFastening.com
www.AerosmithFastening.com

PT2000™ AeroGOLD
The New Gold Standard for
Pressure Treated Lumber Fastening

VERSAPIN™

FASTENING SYSTEM

.100 Series Knurled Shank Wire Coil Collated

Pin Specs


Shank Diameter = .100"
 Head Diameter = .250 2385AG/2635SBG = .312
 PT2000 Plating

TOOL GROUP A

Aerosmith – ST4100, ST4200

TOOL GROUP S

Aerosmith - ST565
 MAX – CN565S
 Hitachi – NV65AC, NV65AH, NV75AG
 Bostitch – N75C, N89C-1



ST4200



ST565

ITEM	LENGTH	KNURL	MIL (GAUGE) 33ksi)	CARTON	TOOL GROUP	COIL SIZE
2352AG	1-3/8" (35mm)	Gripshank®	54-43 (16-18)	2 M	A	200 Pins
2352SG	1-3/8" (35mm)	Gripshank®	54-43 (16-18)	4 M	S	250 Pins
2385AG	1-1/2" (38mm)	Gripshank®	54-43 (16-18)	2M	A	200 Pins
2501SG	2" (51mm)	Helical	97-54 (12-16)	3 M	S	250 Pins
2502SG	2" (51mm)	Gripshank®	54-43 (16-18)	3 M	S	250 Pins
2631SG	2-1/2" (64mm)	Helical	97-54 (12-16)	2.4 M	S	300 Pins
2635SBG	2-1/2" (64mm)	Gripshank®	54-43 (16-18)	2.4M	SB	250 Pins

SUREPIN™

FASTENING SYSTEM

.144 Series Smooth and Helical Shank Plastic Strip

Pin Specs

Shank Diameter = .144"
 Head Diameter = .300"
 PT2000 Plating



Aerosmith CT90

ITEM	LENGTH	SUGGESTED NOSE	CARTON	KNURL	COLLATION
5574PG	2-1/4" (57mm)	503-63-COL	2.4 M	Helical	Plastic Strip

PowerPIN™

.144 Series Smooth and Helical Shank Plastic Sheet Collation

Pin Specs

Shank Diameter = .145"
 Head Diameter = .300"
 PT2000 Plating



HN120

ITEM	LENGTH	KNURL	CARTON	COIL SIZE
5323HPG	1-1/4" (32mm)	Smooth	1.5 M	75 Pins
5573HPG	2-1/4" (57mm)	Smooth	1 M	50 Pins

PT2000™ AeroGOLD
 The New Gold Standard for
 Pressure Treated Lumber Fastening

Member of
Steel Framing Alliance™



Aerosmith Fastening Systems (Aerosmith) does not practice structural engineering, or architectural / building design, and is not responsible for the recommendation or use of its products in situations where a professional or certified opinion is required. It is the responsibility of the end user to comply with all local building codes, project design specifications, and good building practices. For the use of building professionals, Aerosmith does provide third party evaluation reports and engineered test data performed to recognized protocols.