

Aerosmith High Pressure Concrete Pins





HN25C

Benefits of Aerosmith Pins with Your High Pressure Tools

- † Precast slabs & Lintels
- † Up to 3/16" Red Iron Steel
- † 3,500-7,000 PSI Concrete (2193HPST)
- † Perfect for all types of wood to concrete including 5/8" and 3/4"
- † Pressure Treated or ACQ 2x4
- † ICBO/ICC Evaluation Reports
- † No Licensing Required
- † No Batteries or Gas to worry about
- † Just plug into a 15amp outlet and lay track as Fast as you can!
- † Less Tool Maintenance
- † Lighter, Faster, Easier to use overhead
- † High capacity coil (75-100 pins per coil)


Call 1-800-528-8183 or visit us online at www.AerosmithFastening.com.

**Do You Have Concrete....
Do You Have Track...
You Need Aerosmith High Pressure Pins!!**



Aerosmith pins ensure consistent and durable fastening.

3,500-7,000 PSI
Concrete Step Pin
(2193HPST)



CFS Steel to
Structural Steel




Plywood
to Concrete



An **aerosmith**® Product...

*Redefining the Standard
for Concrete Fastening*

Your Local Aerosmith Distributor:



Use Aerosmith Pins in your High Pressure Tools

Aerosmith has pins for your High Pressure tools. .100 Series pins were custom designed for use with the MAX HN25C High Pressure Tool. The .145 Series high pressure pins for use the the MAX HN120 High Pressure tool for attaching plywood and 2x4's to concrete.



PER Report
07021
ICC ESR-3453
LARR 25264

Reports and Approvals
Available at
www.AerosmithFastening.com

.100 Series, Knurled and Smooth Shank Plastic Sheet Coil Collated

Shank Diameter = .109" Head Diameter = .250" Zinc Galvanized

ITEM	LENGTH	KNURL	CARTON	APPLICATION	STEEL
2193HPST	3/4" (19mm) .104/.118 Shank Diameter	SMOOTH	2 M	3,500-7,000 PSI concrete, precast slabs, lentils and track to up to 3/16" red iron	43-27mil (18-24ga)

.145 Series, Knurled and Smooth Shank Plastic Sheet Coil Collated

Shank Diameter = .145" Head Diameter = .300" Zinc Galvanized PG pins PT2000 Galvanized

ITEM	LENGTH	KNURL	CARTON	APPLICATION
5253HP	1" (25mm)	SMOOTH	1.5 M	STEEL TRACK
5323HP	1-1/4" (32mm)	SMOOTH	1.5 M	PLYWOOD
5323HPG	1-1/4" (32mm)	SMOOTH	1.5 M	PREMIUM GALV. FOR CFB TO BLOCK
5383HP	1-1/2" (38mm)	SMOOTH	1.5 M	PLYWOOD
5503HP	2" (51mm)	SMOOTH	1.5 M	CFB TO FOAM TO CONCRETE
5573HP	2-1/4" (57mm)	SMOOTH	1 M	SLEEPER / DIM. LUMBER
5573HPG	2-1/4" (57mm)	SMOOTH PT2000	1 M	ACQ 2x4 CONCRETE
5633HPG	2-1/2" (63mm)	SMOOTH PT2000	1 M	ACQ 2x4 TO CONCRETE

Tool Features and Accessories



Swivel Hose
Fitting



HN25C Dial Adjustable
Depth Control



Air Hose and Fittings

High pressure hose and fittings are designed exclusively for High Pressure tools. 100 ft./30 mm and 50 ft./30 mm High Pressure Hose



400 PSI Compressor
High pressure compressor designed to operate High Pressure tools.

Your Local Aerosmith Distributor:

Aerosmith Fastening Systems
5621 Dividend Road, Indianapolis, IN 46241
Ph: 317.243.5959 Fax: 317.390.6980
Email: info@AerosmithFastening.com
www.AerosmithFastening.com

Aerosmith Fastening Systems (Aerosmith) does not practice structural engineering, or architectural / building design, and is not responsible for the recommendation or use of its products in situations where a professional or certified opinion is required. It is the responsibility of the end user to comply with all local building codes, project design specifications, and good building practices. For the use of building professionals, Aerosmith does provide third party evaluation reports and engineered test data performed to recognized protocols.

Reorder Number: HPCConcrete 2-14