



**Recommended Aerosmith Versapin<sup>®</sup> Fasteners And Tools  
For The Installation Of BASF Permalath<sup>®</sup> To Cold-Formed Steel**

ITEM	LENGTH		Gauge of	CARTON			Tool	Magnetic
#	INCHES	KNURL	Steel Range (33KSI) <sup>(3)</sup>	QTY	WT	COIL SIZE	Needed	Washer Adapter #
2352A	.100x1-3/8"	GRIPSHANK	14 - 20	2M	9.2	200-WIRE	ST4100	UNM4100A
2352AG <sup>(1)</sup>	.100x1-3/8"	GRIPSHANK	14 - 20	2M	9.2	200-WIRE	ST4100	UNM4100A
2352S	.100x1-3/8"	GRIPSHANK	14 - 20	4M	15	250-WIRE	CN-565S	UNM565
2352SG <sup>(1)</sup>	.100x1-3/8"	GRIPSHANK	14- 20	4M	15	250-WIRE	CN-565S	UNM565
2359N	.100x1-3/8"	GRIPSHANK SS <sup>(2)</sup>	16 (33KSI) - 22 (50KSI)	3.2M	14.2	200-PLASTIC SHEET	CN-565S	UNM565
2389N	.100x1-1/2"	GRIPSHANK SS <sup>(2)</sup>	16 (33KSI) - 22 (50KSI)	3.2M	15	200-PLASTIC SHEET	CN-565S	UNM565
2382A	.100X1-1/2"	GRIPSHANK	14- 20	2M	9	200-WIRE	ST4100	UNM4100A
2502S	.100x2"	GRIPSHANK	14- 20	3M	15.5	250-WIRE	CN-565S	UNM565
2502SG <sup>(1)</sup>	.100x2"	GRIPSHANK	14- 20	3M	15.5	250-WIRE	CN-565S	UNM565

Notes:

1. PT2000 coated. PT2000 provides an ASTM B117 Salt Spray value of 2190 Hours; more than 3X the value provided by Hot Dipped Galvanization
2. Gripshank SS - Designed specifically for thin steel. This is a modified point and collation for attaching material to 22ga (50KSI). It works down to 16ga (33KSI).
3. Recommendations generally based on the use of 33KSI steel. 50KSI steel and stronger can alter the range of gauge compatibility.