



NOTE

1-THE MOUNTING HOLE DIA REQUIRED TO MOUNT THE CALLBOX, DEPENDS ON THE ACCURACY OF THE MOUNTING HOLE LOCATIONS. IF THE HOLE DIAMETERS GET TO BIG TO PROVIDE ADEQUATE MATERIAL FOR THE FASTENER HEAD TO CLAMP AGAINST, THEN A LARGER DIAMETER FLAT WASHER SHOULD BE USED TO CLAMP THE CALLBOX AGAINST THE MOUNTING SURFACE. THE MOUNTING HOLES ARE CLEARANCE HOLES FOR #10-32 SCREWS. THE MAXIMUM SCREW INSERTION DEPTH INTO THE CASE IS 5/16"

B	A	REV	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	APPROVALS	DATE	RITRON INC.			
		RELEAS		EDN	DRAWN	G. KING	8/25/00	505 W. CARMEL DR., CARMEL, IN 46032	
B	A	REV	TOLERANCES ARE: (EXCEPT AS NOTED) FRACTIONS	CHECKED		CALLBOX-XT MOUNTING HOLE PATTERN			
		RELEAS		EDN	ISSUED		SIZE	USED ON	DWG. NO.
B	A	REV	DECIMALS	MATERIAL	SEE NOTE	D		REFERENCE DWG	B
		RELEAS	EDN	FINISH	SEE NOTE	SCALE	FILE NO.		
		DATE	ANGLES	DO NOT SCALE DRAWING		1:1	CALLBOX-XT Mounting hole pattern	SHEET 1 OF 1	