

Model

eikon[™] e6

eб

Project: Item:

Quantity: Approval:

Date:



Standard Features

- Advanced Cooking Technology^{*} with planar plume, radiant and microwave technologies for faster, even heating and browning
- "Ventless^{*} Cooking" capabilities through built-in catalytic converter with full protein capabilities
- Ability to use a standard metal baking pan while in convection/microwave mode
- Automatic voltage detection (U.S. only)
- Up to ten (10) times faster than conventional cooking methods
- Power management system keeps power below 20 or 30 amps.
- Quiet operation maximum noise level of 65 dBA in idle mode

*Local codes prevail. These are the "authority having jurisdiction" as stated by the National Fire Protection Association, Inc., in NFPA96-1994.

Specifications

Construction


- 430 stainless steel casework and 304 stainless steel interior cavity
- Easily removable and cleanable grease and cooling air filters

EasyToUCH[™] Control Panel

- Icon driven, color touch screen control panel with the capability of storing up to 1,024 multi-stage recipe programs
- Each program offers up to six (6) stages with programmable cooking times, microwave power settings and user instructions for each stage
- · Self diagnostics capability to monitor components
- Easy menu updates or data transfer via USB memory stick
- Multi-languages available



The e6 utilizes a new and patented heat transfer method called "planar plumes". Heated air is directed into planes which collide above the food surface and are then drawn around the food.



Merrychef U.S.A 1111 N. Hadley Rd. Ft. Wayne, IN 46804 Tel: 888.417.5462 Fax: 800.285-9511 E-Mail: info@merrychefusa.com www.merrychefusa.com





∽ Merrychef

eikon ™

Overall Size			
Width	24.4"	619.76 mm	
Depth (overall with handle)	30.9″	784.86 mm	
Depth (door open 90 degrees)	41″	1041.4 mm	
Weight	210 lbs.	95 kg	
Oven Cavity Dimensions		1	
Height	10″	254 mm	
Width	14.4″	365.7 mm	
Depth	14.3″	363.2 mm	
Wall Clearance			
Тор	2″	50.8 mm	
Sides	2″	50.8 mm	
Electrical Specifications	20A	Radiant	30A
Phase	1ph	1ph	1ph
Voltage	208/240	208/240	208/240
Frequency	60Hz	60Hz	60Hz
Amperage Requirement	20 Amp	30 Amp	30 Amp
Cord Length	6'	6′	6′
Max Power Rate	4150W	5750W	5720W
Power Output (Microwave)	2000W	2000W	2000W
Power Output (Heater)	3718W	4050W	3718W
Plug		. . .	G •
	NEMA 6-20P	NEMA 6-30P	NEMA 6-30P

Specifications		
Control System	easyToUCH [™] , iconic symbol touch screen control panel	
Cooking Stages	6	
Total Cooking Programs	1024	
Maximum Cooking Time	60 Min	
Defrost	No	
Microwave Distribution System	Rotating Active Antennae	
Magnetron(s)	1	
Display	LCD Backlit	
Interior Light	No	
Automatic Voltage Sensor	Yes	
USB & Menu Updates Software	Yes	
Temperature Range	212-527°F (100-275°C)	
Temperature Increments	1°F	
Air Filter	Yes - Air & grease	
Fan Speed	10%-100%	
Fan Speed Increments	1%	
Microwave Power	0-100%	
Microwave Power Increments	1%	
Rack Option	No	
Turntable	No	
Stackable	No	
Warranty	1 year parts and labor	
Accessories in Box		
Operator Manual/Cleaning Instructions	1 Unit	
Bottle Cleaner	1 Unit	
Bottle Guard	1 Unit	
Trigger Sprays	2 Units	
Cool Down Tray	1 Unit	
USB Menu Key	1 Unit	





For further information on *Merrychef* products and service or advice on which machine suits you best please contact your sales representative or visit our website at www.merrychefusa.com.

Merrychef U.S.A 1111 N. Hadley Rd. Ft. Wayne, IN 46804 Tel: 888.417.5462 Fax: 800.285-9511 E-Mail: info@merrychefusa.com www.merrychefusa.com © 2012 Merrychef U.S.A. 08/12

